

CISCO FIREPOWER 4200 SERIES

FPR4112-NGFW-K9

40G NGFW Firewall · 8x10G SFP+ · 2 NM Bays

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	FPR4112-NGFW-K9
Category	Cisco Firepower 4200 Series
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO FIREPOWER 4200 SERIES

FPR4112-NGFW-K9

40G NGFW Firewall · 8x10G SFP+ · 2 NM Bays

The FPR4112-NGFW-K9 is a Cisco Secure Firewall 4100 Series Firepower 4112 NGFW appliance for internet-edge and data center perimeters that run Threat Defense. The 1RU appliance delivers 19 Gbps of FW + AVC + IPS throughput, 10 million concurrent sessions and 4.5 Gbps of hardware TLS decryption, with eight fixed 1G/10G SFP+ ports and two network module bays.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	FPR4112-NGFW-K9	Product type	Cisco Firepower 4112 NGFW appliance
Firewall model	FPR-4112	Security software role	Cisco Secure Firewall Threat Defense / NGFW
Rack units	1RU	Dimensions	1.75 x 16.89 x 29.7 in. (4.4 x 42.9 x 75.4 cm)
On-chassis data ports	8 x 10 Gigabit Ethernet SFP+	Network module bays	2
Maximum interface expansion	Up to 4 x 100GE QSFP28, 24 x 10GE SFP+, 8 x 40GE QSFP+, or 24 x 1GE ports with network modules and fixed ports	Management port	1 Gigabit Ethernet SFP port
Serial port	1 x RJ-45 console	USB port	1 x USB 2.0
Storage	400 GB	Fan modules	6 hot-swappable fans
Power supply configuration	Single 1100W AC; dual optional; single or dual 950W DC optional	Power redundancy	1+1
AC input voltage	100 to 240V AC	AC maximum output power	1100W
DC input voltage	-40V to -60VDC	DC maximum output power	950W
Firewall throughput	40 Gbps	NGFW throughput	19 Gbps
IPS throughput	19 Gbps	Maximum concurrent connections	10 million
New connections per second	98000 with AVC	TLS throughput	4.5 Gbps
Fixed port transceiver support	1G and 10G SFP/SFP+ options listed for Firepower 4112 fixed ports	Fixed port first supported release	Threat Defense 6.6 / ASA 9.14
Mounting	4-post EIA-310-D rack mount rails included	Weight	17.87 kg (39.4 lb) with 2 power supplies, 2 network modules, and 6 fans
Operating temperature	32 to 104F (0 to 40C)	Operating humidity	5 to 95% noncondensing
Operating altitude	10000 ft maximum		

Get Price and Availability for FPR4112-NGFW-K9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](https://www.whatsapp.com/channel/00253333333333333333) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.

LAYER23-SWITCH