

CISCO FIREPOWER 4200 SERIES

FPR4115-ASA-K9

80G ASA Firewall · 8x10G SFP+ · 2 NM Bays

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	FPR4115-ASA-K9
Category	Cisco Firepower 4200 Series
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO FIREPOWER 4200 SERIES

FPR4115-ASA-K9

80G ASA Firewall · 8x10G SFP+ · 2 NM Bays

The FPR4115-ASA-K9 is a Cisco Firepower 4100 Series ASA firewall appliance for data center and internet-edge boundaries that need 80 Gbps of stateful inspection. The 1RU appliance provides 40 Gbps multiprotocol throughput, 15 million concurrent connections, 15,000 VPN peers, eight 10G SFP+ ports and two network module bays.

New, factory-sealed · [3-year LSCare warranty](#) · [14-day returns](#) · [Cisco SN check before shipment](#)

Specifications

Product ID	FPR4115-ASA-K9	Noise	63 dBA typical; 74 dBA maximum
Product type	Cisco Firepower 4115 ASA appliance	Firewall model	FPR-4115
Rack units	1RU	Memory	192 GB
Dimensions	1.75 x 16.89 x 29.7 in. (4.4 x 42.9 x 75.4 cm)	Weight	17.87 kg (39.4 lb) with 2 power supplies, 2 network modules, and 6 fans
On-chassis data ports	8 x 10 Gigabit Ethernet SFP+	Network module bays	2
Maximum interface expansion	Up to 4 x 100GE QSFP28, 24 x 10GE SFP+, 8 x 40GE QSFP+, or 24 x 1GE ports with network modules and fixed ports	Management port	1 Gigabit Ethernet SFP port
Serial port	1 x RJ-45 console	USB port	1 x USB 2.0
Storage	400 GB	Fan modules	6 hot-swappable fans
Power supply configuration	Single 1100W AC; dual optional; single or dual 950W DC optional	Power redundancy	1+1
AC input voltage	100 to 240V AC	AC maximum output power	1100W
DC input voltage	-40V to -60VDC	DC maximum output power	950W
Stateful inspection firewall throughput	80 Gbps	Multiprotocol firewall throughput	40 Gbps
Concurrent firewall connections	15 million	New connections per second	848K
Firewall latency	3.5 microseconds with UDP 64B test traffic	IPsec VPN throughput	15 Gbps
Maximum VPN peers	15000	Security contexts	10 included; 250 maximum
High availability	Active/active or active/standby	Clustering	Up to 16 appliances
ASA introduction release	ASA 9.12(1) for Firepower 4115 with FXOS 2.6.1 requirement	Fixed port transceiver support	1G and 10G SFP/SFP+ options listed for Firepower 4115 fixed ports
Mounting	4-post EIA-310-D rack mount rails included	Operating temperature	32 to 104F (0 to 40C)

Operating humidity	5 to 95% noncondensing	Operating altitude	10000 ft maximum
Supported SSD	FPR4K-SSD400 for Firepower 4112 and 4115		

Get Price and Availability for FPR4115-ASA-K9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp +86 171 8118 9993 WeChat layer23-switch Telegram @layer23_switch

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.