

CISCO FIREPOWER 4200 SERIES

FPR4125-NGFW-K9

80G NGFW Firewall · 45G NGFW · 800GB SSD

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	FPR4125-NGFW-K9
Category	Cisco Firepower 4200 Series
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO FIREPOWER 4200 SERIES

FPR4125-NGFW-K9**80G NGFW Firewall · 45G NGFW · 800GB SSD**

FPR4125-NGFW-K9 is a Cisco Firepower 4125 NGFW firewall appliance in the Cisco Secure Firewall 4100 Series for Threat Defense deployments at data center, service-provider edge, or high-capacity firewall edge sites.

New, factory-sealed · [3-year LSCare warranty](#) · [14-day returns](#) · [Cisco SN check before shipment](#)

Specifications

Product ID	FPR4125-NGFW-K9	Product Type	Cisco Firepower 4125 NGFW appliance
Firewall Model	FPR-4125	Security Software Role	Cisco Secure Firewall Threat Defense / NGFW
Form Factor	1RU	Memory	192 GB
Storage	800 GB	Dimensions	1.75 x 16.89 x 29.7 in. (4.4 x 42.9 x 75.4 cm)
Weight	39.4 lb (17.87 kg) with 2 power supplies, 2 network modules, and 6 fans	On-chassis Data Ports	8 x 1/10 Gigabit Ethernet SFP+
Network Module Bays	2	Maximum Interface Expansion	Up to 4 x 100GE QSFP28, 24 x 10GE SFP+, 8 x 40GE QSFP+, or 24 x 1GE ports with network modules and fixed ports
Management Port	1 Gigabit Ethernet SFP port	Management Optics	Supports 1Gbps fiber or copper optical modules
Serial Port	1 x RJ-45 console	USB Port	1 x USB 2.0
Airflow	Front to rear	Firewall Performance Summary	80 Gbps
FW + AVC Throughput	45 Gbps	FW + AVC + IPS Throughput	45 Gbps
NGIPS Throughput	45 Gbps	Maximum Concurrent Sessions with AVC	25 million
New Connections Per Second with AVC	269K	TLS Throughput	8.5 Gbps
IPsec VPN Throughput	19 Gbps	Maximum VPN Peers	20000
Multi-Instance Capable	Yes	High Availability	Active/Standby with Threat Defense HA configuration
Clustering	Up to 16 appliances with Threat Defense clustering	Centralized Management	Management Center or Cisco Defense Orchestrator
Fixed Port Transceiver Support	1G and 10G SFP/SFP+ options listed for Secure Firewall 4100 fixed ports	Power Supply Configuration	Dual 1100W AC
Power Redundancy	1+1	AC Input Voltage	100 to 240V AC
AC Maximum Output Power	1100W	DC Input Voltage	-40V to -60VDC

DC Maximum Output Power	950W	Fan Modules	6 hot-swappable fans
Fan Redundancy	5+1	Rack Mount	4-post EIA-310-D rack mount rails included
NEBS Operation	Supported on FPR-4125 platform	Operating Temperature	32 to 104F (0 to 40C) or NEBS operation profile for FPR-4125
Operating Humidity	5 to 95% noncondensing	Operating Altitude	10000 ft maximum; 13000 ft maximum under FPR-4125 NEBS operation
Noise	63 dBA typical; 74 dBA maximum	Supported SSD	FPR4K-SSD800 for Firepower 4125 and 4145
Supported Power Cord Rule	Only approved power cords or jumper power cords provided with the security appliance are supported		

Get Price and Availability for FPR4125-NGFW-K9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](https://www.whatsapp.com/channel/0025-v3090-23090) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.