

CISCO FIREPOWER 4200 SERIES

FPR4145-ASA-K9

80G ASA Firewall · 50G Multiprotocol · 384GB Memory

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	FPR4145-ASA-K9
Category	Cisco Firepower 4200 Series
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO FIREPOWER 4200 SERIES

FPR4145-ASA-K9

80G ASA Firewall · 50G Multiprotocol · 384GB Memory

FPR4145-ASA-K9 is a Cisco Firepower 4145 ASA firewall appliance in the Firepower 4100 Series, built as a 1RU security platform for data center and enterprise edge ASA deployments.

New, factory-sealed · [3-year LSCare warranty](#) · [14-day returns](#) · [Cisco SN check before shipment](#)

Specifications

Product ID	FPR4145-ASA-K9	Product Type	Cisco Firepower 4145 ASA appliance
Firewall Model	FPR-4145	Security Software Role	Cisco Secure Firewall ASA
Form Factor	1RU	Memory	384 GB
Storage	800 GB	Dimensions	1.75 x 16.89 x 29.7 in. (4.4 x 42.9 x 75.4 cm)
Weight	39.4 lb (17.87 kg) with 2 power supplies, 2 network modules, and 6 fans	On-chassis Data Ports	8 x 1/10 Gigabit Ethernet SFP+
Network Module Bays	2	Maximum Interface Expansion	Up to 4 x 100GE QSFP28, 24 x 10GE SFP+, 8 x 40GE QSFP+, or 24 x 1GE ports with network modules and fixed ports
Management Port	1 Gigabit Ethernet SFP port	Management Optics	Supports 1Gbps fiber or copper optical modules
Serial Port	1 x RJ-45 console	USB Port	1 x USB 2.0
Airflow	Front to rear	Stateful Inspection Firewall Throughput	80 Gbps
Multiprotocol Firewall Throughput	50 Gbps	Concurrent Firewall Connections	40 million
New Connections Per Second	1.5 million	Firewall Latency	3.5 microseconds with UDP 64B test traffic
IPsec VPN Throughput	23 Gbps	Maximum VPN Peers	20000
Security Contexts	10 included; 250 maximum	High Availability	Active/active or active/standby
Clustering	Up to 16 appliances	Centralized Management	Cisco Security Manager or Cisco Defense Orchestrator
Local Management	Adaptive Security Device Manager	Minimum 100G Module Software	FPR4K-NM-2X100G first supported in Threat Defense 7.3.1 and ASA 9.18.1
Current Compatibility Example	FXOS 2.17 supports ASA 9.23 9.22 9.20 9.19 and 9.18 on Firepower 4145	Power Supply Configuration	Dual 1100W AC
Power Redundancy	1+1	AC Input Voltage	100 to 240V AC
AC Maximum Output Power	1100W	DC Input Voltage	-40V to -60VDC
DC Maximum Output Power	950W	Fan Modules	6 hot-swappable fans

Fan Redundancy	5+1	Rack Mount	4-post EIA-310-D rack mount rails included
Operating Temperature	32 to 104F (0 to 40C) at sea level	Operating Humidity	5 to 95% noncondensing
Operating Altitude	10000 ft maximum	Noise	63 dBA typical; 74 dBA maximum
Supported SSD	FPR4K-SSD800 for Firepower 4125 and 4145		

Get Price and Availability for FPR4145-ASA-K9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](https://www.whatsapp.com/channel/0025-v3017-23017-23017) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.