

CISCO FIREPOWER 4200 SERIES

FPR4145-NGFW-K9

80G NGFW Firewall · 53G NGFW · 384GB Memory

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	FPR4145-NGFW-K9
Category	Cisco Firepower 4200 Series
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO FIREPOWER 4200 SERIES

FPR4145-NGFW-K9

80G NGFW Firewall · 53G NGFW · 384GB Memory

FPR4145-NGFW-K9 is a Cisco Firepower 4145 NGFW firewall appliance in the Cisco Secure Firewall 4100 Series, built for Threat Defense firewall and security-services deployments at the data center or high-capacity network edge.

New, factory-sealed · 3-year LSCare warranty · 14-day returns ·
Cisco SN check before shipment

Specifications

Product ID	FPR4145-NGFW-K9	Product Type	Cisco Firepower 4145 NGFW appliance
Firewall Model	FPR-4145	Security Software Role	Cisco Secure Firewall Threat Defense / NGFW
Form Factor	1RU	Memory	384 GB
Storage	800 GB	Dimensions	1.75 x 16.89 x 29.7 in. (4.4 x 42.9 x 75.4 cm)
Weight	39.4 lb (17.87 kg) with 2 power supplies, 2 network modules, and 6 fans	On-chassis Data Ports	8 x 1/10 Gigabit Ethernet SFP+
Network Module Bays	2	Maximum Interface Expansion	Up to 4 x 100GE QSFP28, 24 x 10GE SFP+, 8 x 40GE QSFP+, or 24 x 1GE ports with network modules and fixed ports
Management Port	1 Gigabit Ethernet SFP port	Management Optics	Supports 1Gbps fiber or copper optical modules
Serial Port	1 x RJ-45 console	USB Port	1 x USB 2.0
Airflow	Front to rear	Firewall Performance Summary	80 Gbps
NGFW Performance Summary	53 Gbps	IPS Performance Summary	55 Gbps
FW + AVC Throughput	53 Gbps	FW + AVC + IPS Throughput	53 Gbps
NGIPS Throughput	55 Gbps	Maximum Concurrent Sessions with AVC	30 million
New Connections Per Second with AVC	365K	TLS Hardware Decryption Throughput	10 Gbps
IPsec VPN Throughput	24 Gbps	Maximum VPN Peers	20000
Multi-Instance Capable	Yes	High Availability	Active/Standby with Threat Defense HA configuration
Clustering	Up to 16 appliances or instances with Threat Defense clustering	Centralized Management	Management Center or Cisco Defense Orchestrator
Trust Anchor Technologies	Included on Cisco Secure Firewall 4100 Series platforms	Minimum 100G Module Software	FPR4K-NM-2X100G first supported in Threat Defense 7.3.1 and ASA 9.18.1
Supported 100G Module	FPR4K-NM-2X100G 2-port 100-Gbps single-wide network module	Power Supply Configuration	Dual 1100W AC

Power Redundancy	1+1	AC Input Voltage	100 to 240V AC
AC Maximum Output Power	1100W	DC Input Voltage	-40V to -60VDC
DC Maximum Output Power	950W	Fan Modules	6 hot-swappable fans
Rack Mount	4-post EIA-310-D rack mount rails included	Operating Temperature	32 to 104F (0 to 40C) at sea level
Operating Humidity	5 to 95% noncondensing	Operating Altitude	10000 ft maximum
Noise	63 dBA typical; 74 dBA maximum	Supported SSD	FPR4K-SSD800 for Firepower 4125 and 4145
Power Cord Rule	Appropriate regional power cord selection is required when an optional cord is not ordered with the system		

Get Price and Availability for FPR4145-NGFW-K9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](https://www.whatsapp.com/channel/00291111111111111111) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.