

CISCO FIREPOWER 4200 SERIES

FPR4215-NGFW-K9

65G NGFW · 8x25G SFP28 Data + 2x25G SFP28 Mgmt · 4200 · NGFW Firewall

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	FPR4215-NGFW-K9
Category	Cisco Firepower 4200 Series
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO FIREPOWER 4200 SERIES

FPR4215-NGFW-K9

65G NGFW · 8x25G SFP28 Data + 2x25G SFP28 Mgmt · 4200 · NGFW Firewall

FPR4215-NGFW-K9 is the Cisco Secure Firewall 4215 NGFW appliance in the Secure Firewall 4200 Series, built as a 1RU Threat Defense firewall for high-throughput edge and data center security services. Cisco identifies this SKU as the 4215 NGFW orderable appliance with two network module bays, eight fixed 1/10/25G SFP28 data ports, two 1/10/25G SFP28 management ports, and 256 GB of system memory.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	FPR4215-NGFW-K9	Product Type	Cisco Secure Firewall 4215 NGFW appliance
Firewall Model	Secure Firewall 4215	Security Software Role	Cisco Secure Firewall Threat Defense / NGFW
Form Factor	1RU	Rack Mount	4-post EIA-310-D rack with slide rails
Airflow	Front to rear; I/O side to non-I/O side	System Memory	256 GB
Storage	Two 1.8 TB NVMe SSD slots; ships with two 1.8 TB SSDs in RAID1	Fixed Data Ports	8 x 1/10/25-Gbps SFP28 fixed fiber ports
Fixed Port Names	Ethernet 1/1 through Ethernet 1/8	Management Ports	2 x 1/10/25-Gbps SFP28 ports
Management Model	Firewall Management Center or Cisco Defense Orchestrator	Network Module Slots	2 hot-swappable slots
Supported Module Speeds	1G 10G 25G 40G 100G 200G and 400G module options	Console Port	1 x RJ-45 serial port
USB Port	1 x USB 3.0 Type A port	FW + AVC Throughput	65 Gbps
FW + AVC + IPS Throughput	65 Gbps	NGIPS Throughput	65 Gbps
Maximum Concurrent Sessions with AVC	15 million	New Connections Per Second with AVC	350K
TLS Hardware Decryption Throughput	20 Gbps	IPsec VPN Throughput	45 Gbps
Maximum VPN Peers	20000	Multi-Instance Count	10
High Availability	Active/active with clustering and active/standby	Clustering	Up to 16 chassis
AVC Support	Standard; more than 4000 applications	Cisco Secure IPS	Available
Cisco Malware Defense	Available	URL Filtering Categories	More than 120
URL Filtering Database	More than 280 million categorized URLs	Default Power Supply	FPR4200-PWR-AC 1900W AC module
Redundant Power Rule	Second power supply must be ordered for redundant power on 4215	AC Input Voltage	100 to 120 VAC low line or 200 to 240 VAC high line

AC Frequency	50/60 Hz nominal	AC Maximum Input Power	770 W for 4215
AC Efficiency	More than 90 percent Platinum	Fan Modules	Three dual fan modules; hot-swappable
Chassis Weight	43 lb (19.5 kg) with 2 power supplies, 2 network modules, and 3 fan modules	Chassis Dimensions	1.73 x 16.89 x 32.0 in. (4.39 x 42.9 x 81.28 cm)
Operating Temperature	32 to 104F (0 to 40C)	Operating Humidity	5 to 90% noncondensing
Operating Altitude	0 to 10000 ft (0 to 3048 m)	NEBS Operation	Supported on FPR 4215
NEBS Operating Altitude	0 to 13000 ft (3960 m)	Sound Pressure	<=78 dBA typical; <=84 dBA maximum
Supported Power Cord Rule	Only approved power cords or jumper cords provided with Secure Firewall 4200 are supported		

Optional Add-ons

Add-on	Cisco PID	Purpose
Optics	SFP-10G-SR-S	10GBASE-SR SFP+ - S-Class - 400m OM4 MMF
Optics	SFP-10G-LR-S	10GBASE-LR SFP+ - S-Class - 10km SMF
Optics	SFP-25G-SR-S	25GBASE-SR SFP28 - 850nm MMF - 100m OM4
Optics	SFP-10/25G-CSR-S	10/25GBASE-CSR SFP28 - 850nm 400m MMF Transceiver
Optics	SFP-10/25G-LR-S	10/25GBASE-LR SFP28 - 10 km G.652 SMF - 0 to 70°C Commercial Temperature
Optics	GLC-LH-SMD	1000BASE-LX/LH SFP - 10km SMF / 550m MMF - DOM
Optics	GLC-TE	1000BASE-T SFP - RJ-45 Cat5 Copper - 100m Reach
Optics	GLC-SX-MMD	1000BASE-SX SFP - MMF 850nm - DOM

Get Price and Availability for FPR4215-NGFW-K9

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)
[View Product Page](#)


Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](https://www.whatsapp.com/channel/0025-v3070123456789) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.