

CISCO ISR 4000 ROUTER MODULES & CARDS

NIM-4T

4-Port Serial WAN · Smart Serial NIM · 8 Mbps

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	NIM-4T
Category	Cisco ISR 4000 Router Modules & Cards
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO ISR 4000 ROUTER MODULES & CARDS

NIM-4T

4-Port Serial WAN · Smart Serial NIM · 8 Mbps

NIM-4T is a Cisco 4400 Series ISR 4-port multi-protocol synchronous serial WAN network interface module for branch routers that need to terminate multiple legacy serial handoffs from one NIM slot, combining four Smart Serial 12-in-1 connectors with up to 8 Mbps per port, support for V.35, RS-232, X.21, RS449, RS530, and RS530A interfaces, and Cisco-documented HDLC, PPP, and Frame Relay encapsulation for point-to-point or Frame Relay WAN deployments.

New, factory-sealed · 3-year LSCare warranty · 14-day returns ·
Cisco SN check before shipment

Specifications

Product ID	NIM-4T	Product type	Synchronous serial WAN NIM
Cisco description	4-Port Serial WAN Interface Card	Connector type	Smart Serial / 12-in-1
Connector count	4	Ports per connector	1
Maximum data rate per port	8 Mbps	Supported interfaces	V.35, RS-232, X.21, EIA/TIA-449, EIA-530, and EIA-530A
Supported encapsulations	HDLC, PPP, and Frame Relay	Synchronous support	Yes
4400 Series software baseline	Cisco IOS XE Release 3.12S or later	Feature set baseline	IP Base feature set
Physical form factor	Singlewide NI, no slot restrictions	Supported platform quantity in datasheet	Up to 3 modules on Cisco 4451-X
Clock rate range	1200 to 8000000 bps for DCE interfaces	Default MTU	1500 bytes
MTU range	64 to 8100 bytes	Half duplex support	Not supported
Physical dimensions	1.25 x 3.50 x 7.24 in. (3.18 x 8.89 x 18.39 cm)	Operating temperature	32 to 104 degrees F (0 to 40 degrees C)
Storage temperature	-4 to 149 degrees F (-20 to 65 degrees C)	Relative humidity	10 to 90 percent, noncondensing

Get Price and Availability for NIM-4T

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](tel:+8617181189993) WeChat [layer23-switch](#) Telegram [@layer23_switch](#)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.