

CISCO · CATALYST 9000 SWITCH POWER SUPPLY

PWR-C5-715WDC

715W DC PSU · Catalyst 9200L PoE Spare

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	PWR-C5-715WDC
Category	Catalyst 9000 Switch Power Supply
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · CATALYST 9000 SWITCH POWER SUPPLY

PWR-C5-715WDC

715W DC PSU · Catalyst 9200L PoE Spare

PWR-C5-715WDC is a Cisco Catalyst 9200 Series 715W DC Config 5 power supply module used as a spare DC input supply for Catalyst 9200 and Catalyst 9200L PoE switch power bays.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	PWR-C5-715WDC	Cisco ordering form	PWR-C5-715WDC=
Product type	DC power supply module	Cisco description	715W DC Config 5 Power Supply
Ordering status	Spare only	Supported platform scope	PWR-C5-715WDC and PWR-C6-715WDC spare family supported only on C9200L and C9200 PoE models
Minimum software support	Cisco IOS XE 17.8.1 and later	C9200L 24-port DC PoE rows	C9200L-24P-4G, C9200L-24P-4X, C9200L-24PXG-4X, and C9200L-24PXG-2Y
C9200L 48-port DC PoE rows	C9200L-48P-4G, C9200L-48P-4X, C9200L-48PL-4G, C9200L-48PL-4X, C9200L-48PXG-4X, and C9200L-48PXG-2Y	Rated maximum output	715W
Total output BTU	2440 BTU/hr, 715W	Input voltage range	-40 to -72 VDC
Input current	20-11.3A	Output ratings	55V at 13.25A; 5V at 0.3A
Output holdup time	2 ms minimum at -40 VDC	Input receptacle	Terminal block
Power feed rating	25A	Physical dimensions	1.6 x 4.0 x 7.1 in. (H x W x D)
Weight	3.5 lb (1.59 kg)	Power supply slots	Two power supply slots on Catalyst 9200 switch chassis
Slot population rule	Each power supply slot must contain a power supply or a blank module	FRU behavior	Main module field replaceable; redundant module hot-swappable
Power module fan note	All power supply modules except blank modules have internal fans	AC and DC mix note	PWR-C5-715WDC and PWR-C6-715WDC can mix with AC power supplies as primary or secondary on the same C9200L or C9200 device
Available PoE with one DC PSU	485W on listed PoE models	Second DC PSU on 24-port rows	740W on listed 24-port PoE rows
Second DC PSU on 48-port rows	970W on listed 48-port PoE rows		

Get Price and Availability for PWR-C5-715WDC

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](https://www.whatsapp.com/channel/0025-v3017-23017-23017) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.

LAYER23-SWITCH