

CISCO · SWITCHES

PWR-IE240W-PCAC-L

240W AC PSU · 54V PoE Output · Hardwired DIN-Rail

New, factory-sealed · 3-year LSCare warranty · Ships from Hong Kong and US stock



Product Model	PWR-IE240W-PCAC-L
Category	Switches
Condition	New, factory-sealed
Warranty	3-year LSCare warranty
Supplier	Layer23-Switch · www.layer23-switch.com



Scan for price and stock

200+

Countries Served

18,000+

Customers Worldwide

US\$9M+

Ready-Stock Inventory

3-Year

Warranty



CISCO · SWITCHES

PWR-IE240W-PCAC-L

240W AC PSU · 54V PoE Output · Hardwired DIN-Rail

PWR-IE240W-PCAC-L is a Cisco Industrial DIN-rail 240W AC-to-DC PoE power supply for industrial Ethernet switch power designs. Cisco lists the orderable PID as PWR-IE240W-PCAC-L=, with hardwired AC input, 90-264V AC supported input range, 54V DC output across a 48-56V DC range, 4.5A output current, and IP20 enclosure rating.

New, factory-sealed · 3-year LSCare warranty · 14-day returns · Cisco SN check before shipment

Specifications

Product ID	PWR-IE240W-PCAC-L	Cisco ordering part	PWR-IE240W-PCAC-L=
Product type	240W AC-to-DC PoE power supply	Ordering description	240W AC to DC power supply
Input connection type	Hardwired	PoE support	Yes
Rated nominal input	AC 100-240V/3.5A, 50-60Hz	Supported input range	AC 90-264V
Typical efficiency	91%	Inrush current	<35A at 115VAC and 230VAC
Output rating	54VDC / 48-56VDC, 4.5A	Maximum output power	240W
Holdup time at 100% load	20ms	IP rating	IP20
Operating temperature	-40C to +80C	Storage temperature	-40C to +85C
Power derating	Vertical above 50C by 2.5%/C; horizontal above 40C by 2.5%/C	Operating humidity	5 to 95% RH, non-condensing
Dimensions	85 x 121 x 124.1 mm; 3.34 x 4.76 x 4.88 in.	Unit weight	2.11 lb (0.96 kg)
MTBF	1,579,900 hours	Hazardous-location note	Not approved for hazardous-location installations
Conformal coating note	Conformally-coated power supply	Electric safety entries	UL/cUL recognized to UL 60950-1 and UL 62368-1; CB scheme to IEC 60950-1
Industrial safety entries	UL 508 and CSA C22.2 No. 107.1-01	IE2000 table context	Listed as 240W PoE-capable power-supply option
Catalyst IE3200 table context	Listed as 240W PoE-capable power-supply option		

Get Price and Availability for PWR-IE240W-PCAC-L

New, factory-sealed units with a 3-year warranty. Our sales team quotes within one business day, and in-stock orders ship within one business day of payment from our Hong Kong and US warehouses.

[Request a Quote](#)

[View Product Page](#)



Email sales@layer23-switch.com WhatsApp [+86 171 8118 9993](https://wa.me/8617181189993) WeChat [layer23-switch](https://www.whatsapp.com/channel/00299a60000000000000000000000000) Telegram [@layer23_switch](https://t.me/layer23_switch)

Address 2810 North Church Street, Suite 89727, Wilmington, DE 19802, USA

Cisco and Cisco product names are trademarks of Cisco Systems, Inc. Specifications are summarized from manufacturer documentation for reference; confirm the exact configuration with Layer23-Switch before ordering. Revised October 2026.

LAYER23-SWITCH